

EDCO CONCRETE SAWS

COMPACT

FOR ALL ASPHALT AND CONCRETE CUTTING

LIGHTWEIGHT

ECONOMICAL

**Model
SB-12**



USE ABRASIVE OR DIAMOND BLADES



**Model
SB-14**

The EDCO CONCRETE SAWS are specifically designed to fill the need for compact, lightweight units capable of handling the everyday cutting problems of contractors, municipalities, utilities, etc.

The EDCO CONCRETE SAWS rotate in a counter clockwise direction, cutting on the up turn. This method constantly clears the cut, eliminates climb out when a blade begins to get dull and eliminates the need for an air source to clean out the groove.

A folding guide bar is standard equipment on all EDCO saws.


Cut control, attached to the handle, will quickly and easily lower the blade to the proper depth or raise it at the end of the cut. Water feed attachment allows the use of diamond blades. Hub plates are designed with drive pin to retain larger blades, or may be reversed for small diameter blades. This compact, lightweight unit can be lifted on or off a truck by 2 men. Large 8" easy roll, rubber-tired wheels allow maximum maneuverability.

Blade guard tilts back to allow cuts to be made in curbs and walls.

A steel wire brush is available for highway and airport contraction joint cleaning.

use it for

- Highway — Road — Bridge repair
- Cutting trenches for utilities
- Installing traffic control equipment
- Contraction joint sawing & cleaning
- Slab and roof repairing
- Curb and sidewalk repair
- Installation of electrical & plumbing lines



CUT INTO CURBS - WALLS

Model SB-12 Specifications

7 HP gasoline engine • Steel plate welded construction • Heavy duty bearings • Dual belt drive • Adjustable cut control • Water feed attachment • Easy roll 8" wheels • Folding guide bar • Adjustable blade guard • Combination $\frac{3}{4}$ & 1" arbor • Blade guard capacity 14" • Engine efficiency capacity 12" • Depth of cut $3\frac{1}{2}$ " • Height 35" • Width 21" • Length 33" • Weight 226 lbs.

Model SB-14 Specifications

9.5 HP gasoline engine • Steel plate welded construction • Heavy duty bearings • Dual belt drive • Adjustable cut control • Water feed attachment • Easy roll 8" wheels • Folding guide bar • Adjustable blade guard • Combination $\frac{3}{4}$ & 1" arbor • Blade capacity 14" • Depth of cut 5" • Height 35" • Width 21" • Length 33" • Weight 260 lbs.

EQUIPMENT DEVELOPMENT CO. INC.

2700 Garfield Ave. Silver Spring, Md.



CONTRACTOR PRICE LIST
Manufacturers and Developers of Industrial and Construction Equipment

EQUIPMENT DEVELOPMENT COMPANY

CABLE ADDRESS—
"EDCOINC"

JUniper 5-8795
JUniper 5-8798

2700 GARFIELD AVENUE













SILVER SPRING

MARYLAND

Effective June 1, 1964

F.O.B. FACTORY

Prices Subject to Change Without Notice

ITEM OR MODEL	DESCRIPTION	PRICE
 2EC	2EC — CONCRETE GRINDER — Electric, counter-rotating, double disc (circular discs), complete with 1½ HP, single phase, A.C. totally enclosed motor, 110-220 voltage selector switch, on and off switch, extension adapter, 12 2x2x4 grinding stones and supply of wooden wedges. Weight: approx. 225 lbs. Grinding area: approx. 2 sq. ft.	620.00
 2ECW2	2ECW-2 — HYDRO GRINDER — Electric, counter-rotating, double disc, circular or interlocking discs available, 220 volt, 2 HP, single phase, A.C. motor, 4-gallon tank, splash guard, on and off switch, extension adapter, 12 2x2x4 grinding stones, supply of wooden wedges. Weight: 275 lbs. Grinding area: approx. 2 sq. ft.	755.00
 JR	JR — LIGHTWEIGHT CONCRETE GRINDER — Electric, counter-rotating, double disc (interlocking disc), complete with ¾ HP, 110/220 volt, single phase, A.C. completely enclosed motor, on and off switch, extension adapter, 12 3x2x1 grinding stones and supply of wedges. Weight: approx. 99 lbs. Grinding area: approx. 90 sq. in.	430.00
 2GC	2GC — CONCRETE GRINDER — Gasoline, counter-rotating, double disc (circular disc), complete with ¾ HP long-life, cast iron engine (Clinton*), centrifugal clutch, starter rope, 12 2x2x4 grinding stones, supply of wooden wedges. Weight: approx. 200 lbs. Grinding area: approx. 2 sq. ft. *Briggs-Stratton engines optional. Clinton engines shipped unless otherwise specified.	580.00
 2GC6	2GC-6 — XTRA HEAVY DUTY CONCRETE GRINDER — Gasoline, counter-rotating double disc (circular disc) complete with 7 HP gasoline engine, heavy duty centrifugal clutch, dual belt drive, 12 2x2x4 grinding stones, supply of wooden wedges. Approx. weight: 250 lbs. Grinding area: approx. 2 sq. ft.	695.00
 SB-12	SB-12 — CONCRETE SAW — Gasoline, 7 HP Wisconsin engine, dual belt drive, cut control, water feed attachment, folding guide bar, combination adapter hub for ¾" or 1" arbor blades, 1 #302-SB cured concrete abrasive blade included. Weight: 198 lbs.	433.00
 SBE-12	SBE-12 — CONCRETE SAW — Electric motor (3 HP, 220 volt, single phase), dual belt drive, cut control, water feed attachment, folding guide bar, combination adapter hub for ¾" or 1" arbor blades, 1 #302-SB cured concrete abrasive blade included. Weight: 220 lbs.	550.00
 SB-14	SB-14 — CONCRETE SAW — Gasoline, 9.5 HP engine, dual belt drive, cut control, water feed attachment, folding guide bar, adjustable blade guard for curb cutting, combination adapter for ¾" & 1" arbor blades. 1 abrasive blade included. Weight: 250 lbs.	480.00
 SBE-14	SBE-14 — CONCRETE SAW — Electric motor (3 HP, 220 volt, single phase), dual belt drive, cut control, water feed attachment, folding guide bar, adjustable blade guard for curb cutting, combination adapter for ¾" & 1" arbor blades. 1 abrasive blade included. Weight: 235 lbs.	560.00
 CP-5	CP-5 — CONCRETE PLANE — Gasoline, 7 HP Wisconsin engine, variable speed control, 5" wide planer head, quick-disengage lever, fine adjustment depth cut control, 2 sets high carbon steel cutters (fine and coarse). Weight: 275 lbs.	615.00
 CPE-5	CPE-5 — CONCRETE PLANE — Electric motor (3 HP, 220 volt, single phase), on and off switch, extension adapter, quick disengage lever, fine adjustment depth cut control, 5" wide planer head, 2 sets high carbon steel cutters. Weight: 275 lbs.	710.00
 CP-10	CP-10 — CONCRETE PLANE — Gasoline, 7 h.p. engine, dual belt drive, speed control, 10" wide planer head, quick disengage lever, fine adjustment depth cut control, water spray attachment, 2 sets high carbon steel cutters, weight 350 lbs.	775.00
	CP-10 —w/9.5 HP gasoline engine. Specifications same as for CP-10.	825.00
	CPE-10 — CONCRETE PLANE —Specifications same as CP-10 except driven by 3 HP 220 volt single phase motor.	891.00

ITEM OR MODEL

DESCRIPTION

PRICE



2x4 Grinding Stones

Coarse (10 Grit) Medium (24 Grit) Fine (80 Grit)
 Quantities: 1-36 37-124 125 or more
 1.15 ea. 1.00 ea. .85 ea.




3x1 Grinding Stones

.90 ea. .82 ea. .75 ea.


Grinding stones may be assorted for quantity discounts.

Wedge



No. 1 Hardwood Wedges for Model 2EC and 2GC Grinders.

.15 ea.




No. 2 Hardwood Wedges for Model JR Grinder.

.15 ea.

Complete Unit

Scarifier Units, complete (steel case and replaceable cutter assembly). Recommended to be used with circular discs only 6 units per set (complete set).

33.00



Steel Case

Scarifier, steel case only (6 per set)
 (single case)

17.40

2.90



Cutter Assembly

Scarifier, thro-away cutter assembly only (set of 6 units).

Sold only in sets:

1 set

2-5 sets

6 or more sets

15.60 ea.

14.82 ea.

14.04 ea.


Interlocking discs, for 2EC and 2GC machines only. Recommended to be used with grinding stones only; will grind within 3/4 inch of wall. Stones overlap when grinding. Installed at factory, additional per machine:

10.00

Shipped separately, set of 2 discs:

70.00 per set

Interlocking Disc



101-E

Flat wire, Slab and Floor Cleaning Brush, for use with Models 2EC, 2GC, 2ECW2 (Hydro Grinder), 2GC6.

Sold only in sets (6 brushes and 6 wedges per set)

4.50 per set




102-J

Flat wire, Slab and Floor Cleaning Brush, for use with Model JR.

Sold only in sets (6 brushes per set)

4.20 per set



203-CP

Concrete Plane cutter assemblies for Model CP-5 & CP-10 EDCO Concrete Plane, available in fine, medium and coarse.

Cutter assemblies sold only in sets (4 units per set)

Fine

All cutter, no spacing (23 cutters per unit). For solid cutting, removing paint, traffic lines, contraction joint sealer, etc.

29.00 per set

201-CP

Medium

Cutters spaced 1/8 inch apart (14 cutters per unit). For removing high spots, high joints, scarifying prior to patching floors or slabs, etc.

22.00 per set

202-CP

Coarse

Cutters spaced 3/8 inch apart (8 cutters per unit). For removing large amounts of concrete or asphalt, deep scarifying for waterproofing, removing tar and roofing materials.

16.00 per set

203-CP

Components for CP-5 & CP-10 Concrete Plane Cutters.

#CP-401 \$1.00 ea.

Shaft, 6-7/8"
 (Hardened)




#CP-402 \$.06 ea.

Retaining Clip




#CP-403 \$.04 ea.

Spacers



#CP-404 \$.28 ea.

Cutter Wheels



Abrasive Blades for Model SB-12 Concrete Saw, reinforced, safety blade.



302-SB

12" x 3/16" for cutting cured concrete.

303-SB

12" x 3/16" for cutting green concrete (contraction joints).

1-10

7.34

20

7.16

50

6.89

100

6.00



304-SB

Woven, round Wire Brush for Model SB-12 Concrete Saw. Use it for cleaning contraction joints. .035 full cable.

8" DIAMETER

8.80

10" DIAMETER

10.50

12" DIAMETER

15.50